






Code EAN: 3543290005494

Configuration



Bottles capacity with the standard configuration; 5 storing shelves: 225 Bottles*

CONFIGURATION	Storing shelf	Sliding shelf	Capacity*
Optimum Configuration (100% sliding shelves)	-	13	170
Mixt Configuration	2	4	206
Standard Configuration	5	0	225

Oxygen

Gamme: Oxygen

Fonction: Serving (multi-temperatures)

OXGMT225NVND Référence: Equipement: 5 storing shelves 225 Bottles* Capacité:

Constant and reliable temperature thanks to the wine cabinet insulation, the controller and the aluminium walls.

Humidity rate between 65% and 80% ensuring by our product design, the cooling and venting system,

The natural venting system of our wine cabinets ensures constant air renewal within the wine cabinet.

Ideal protection against UV rays thanks to our glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.

No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.

General Features

Dimensions $H \times W \times D$ (mm):	1825 x 680 x 720**	Weight cabinet empty (kg) :	86
Dimensions in pack (mm):	1950 x 720 x 760	Weight equipped cabinet (kg) :	99
Colors:	Black	Weight in pack (kg) :	115
Door:	Glass door black frame	Useful volume (L) :	461

Equipment & Accessories

Equipment

- Glass door with silver frame, integrated handle in the glass frame.
- Glass door with double pan reinforced with gaz argon to filter up to 97% of the UV rays.
- Lock
- Reversible door
- 2 adjustable feet
- Labels for bottles identification

Accessories

Universal shelves: AOHUI Code EAN: 3543290002783

Weight: 2,6 kg

Bottles capacity per level: 12* Material: Solid beech wood.

Modular system: you can choose the shelf configuration:



Sliding shelf « 12 bottles »

The label holder allows you to identify your bottle quickly and easily



Presentation shelf « 6+22 bottles »



Suitable to store all types of bottles



Storing shelf « 72 bottles »



Technical features

Control Panel

Electronic regulation from 6°C to 20°C; From 6°C to 10°C for the lowest part of the cabinet and from 15°C to 20°C for the highest part of the cabinet

- Inner electronic display, Red Leds screen
- Visual for the alarm temperature fault
- Temperature display
- Automatic Winter function

Performances

Cold production: Static cooling Hot production: Heating element

Ensure by the thermodynamical Humidity:

pump system Winter function: Automatic R600a Gaz uses:

Recommended temperature

From 0°C to 30 °C range:

Aluminium Inner material: Insulation type: PU foam Acoustic emissions (db(A)): 37

С Acoustical emission class: 190 Consumption (kWh/year): Energy efficiency rating: G

* Traditional Bordeaux bottles

** With the rear stop, without the handle